

**Direct fastening tools**

DX tool	Vibration			Noise
	Cartridge color	Allowed number of fastenings per day		Workplace relevant emission value L <sub>pA,1s</sub>
		EAV 2.5 m/s <sup>2</sup>	ELV 5 m/s <sup>2</sup>	
GX 120/GX 120 ME	---	3500	14000	102 dB(A)
GX 100/GX 100-E	---	2700	10800	102 dB(A)
DX 351	White	2100	8400	104 dB(A)
	Green	1900	7600	
	Yellow	1100	4400	
	Red	800	3200	
DX 460	Green	1300	5200	103 dB(A)
	Yellow	1000	4000	
	Red	1000	4000	
	Black	600	2400	
DX 76	Blue	700	2800	110 dB(A)
	Red	600	2400	
	Black	400	1600	

\* Sound pressure level L<sub>pA,1s</sub> measured at user's ear according to standard EN 12549. Wear ear plugs according to operating instructions.

DX tool	Vibration			Noise
	Cartridge color	Allowed number of fastenings per day		Workplace relevant emission value L <sub>pA,1s</sub>
		EAV 2.5 m/s <sup>2</sup>	ELV 5 m/s <sup>2</sup>	
DX 860 ENP	Blue	3500	14000	106 dB(A)
	Red	2600	10400	
	Black	1800	7200	
DX 860 HSN	Yellow	5600	22400	100 dB(A)
	Red	5500	22000	
	Black	3000	12000	
DX E72	Brown	1000	4000	109 dB(A)
	Green	900	3600	
	Yellow	700	2800	
DX 36	Green	600	2400	100 dB(A)
	Yellow	500	2000	
	Red	500	2000	

\* Sound pressure level L<sub>pA,1s</sub> measured at user's ear according to standard EN 12549. Wear ear plugs according to operating instructions.

DX tool	Vibration			Noise
	Cartridge color	Allowed number of fastenings per day		Workplace relevant emission value L <sub>pA,1s</sub>
		EAV 2.5 m/s <sup>2</sup>	ELV 5 m/s <sup>2</sup>	
DX A41	Green	1300	5200	103 dB(A)
	Yellow	1000	4000	
	Red	1000	4000	
	Black	600	2400	
DX 750	Blue	600	2400	110 dB(A)
	Red	500	2000	
	Black	400	1600	

\* Sound pressure level L<sub>pA,1s</sub> measured at user's ear according to standard EN 12549. Wear ear plugs according to operating instructions.