


X-M6, X-W6, X-M8, M10, W10 Threaded Studs for Concrete


Product data

Dimensions


X-M6/W6 ____ FP8




X-M8 ____ P8



M10-24-32 P10



W10 ____ P10



General information

Material specifications

Carbon steel shank: HRC 53.5

Zinc coating: 5–20 μm

Recommended fastening tools

DX 460, DX 351, DX 36, DX E72, DX 76,
DX 76 PTR, DX 600 N

See **X-M6, X-W6, X-M8, M10, W10 fastener program** in the next pages and **Tools and equipment chapter** for more details.

Approvals

ICC (USA): **X-W6, W10**


UL, FM: **W10**

Note:


Technical data presented in these approvals and design guidelines reflect specific local conditions and may differ from those published in this handbook.

Applications


Examples




Plates for pipe rings



Hangings with threaded couplers



Electrical boxes



Miscellaneous attachments

Load data

Recommended loads

Fastener designation	Shank diameter d_s [mm]	M_{rec} [Nm]
X-M6/W6	3.7	5.0
X-M8, M10	4.5	9.0
W10	5.2	14.0

X-M6/W6, X-M8, M10, W10


$N_{rec} = V_{rec} =$ 0.4 kN for $h_{ET} \geq 27$ mm

$N_{rec} = V_{rec} =$ 0.3 kN for $h_{ET} \geq 22$ mm

$N_{rec} = V_{rec} =$ 0.2 kN for $h_{ET} \geq 18$ mm


Arrangements to prevent moment on shank:

Coupler tight against concrete



Non-symmetric arrangement:


- Moment on fastened part
- Prying effect must be considered in determining loads acting on fastener



Conditions

- Minimum 5 fastenings per fastened unit (normal weight concrete)
- All visible failures must be replaced.
- With lightweight concrete base material and greater loading may be possible, please contact Hilti.
- Predominantly static loading.
- Observance of all application limitations and recommendations.
- The recommended loads in the table refer to the resistance of the individual fastening and may not be the same as the loads F_N and F_V acting on the fastened part.

Note: If relevant, prying forces need to be considered in design, see example. Moment acting on fastener shank only in case of a gap between base and fastened material.



F

Application requirements

Thickness of base material

Concrete

$h_{\min} = 80 \text{ mm}$ ($d_{\text{nom}} = 3.7 \text{ mm}$)

$h_{\min} = 100 \text{ mm}$ ($d_{\text{nom}} \geq 4.5 \text{ mm}$)

Thickness of fastened material

M6: $t_f \leq L_g - t_{\text{washer}} - t_{\text{nut}} \cong \text{up to } 15 \text{ mm}$

W6: $t_f \leq L_g - t_{\text{washer}} - t_{\text{nut}} \cong \text{up to } 33 \text{ mm}$

M8: $t_f \leq L_g - t_{\text{washer}} - t_{\text{nut}} \cong \text{up to } 15 \text{ mm}$

M10: $t_f \leq L_g - t_{\text{washer}} - t_{\text{nut}} \cong \text{up to } 19 \text{ mm}$


W10: $t_f \leq L_g - t_{\text{washer}} - t_{\text{nut}} \cong \text{up to } 25 \text{ mm}$

Spacing and edge distances (mm)

Pairs


Row along edge

General (e.g. group of fasteners)




Reinforced * Non-reinforced

c 100 150



Reinforced * Non-reinforced

c 80 150



Reinforced * Non-reinforced

c 80 150

a 80 100

* Minimum $\varnothing 6$ reinforcing steel continuous along all edges and around all corners. Edge bars must be enclosed by stirrups.

Corrosion information

The intended use only comprises fastenings which are not directly exposed to external weather conditions or moist atmospheres. For further detailed information on corrosion see relevant chapter in **Direct Fastening Principles and Technique** section.

Fastener selection and system recommendation

Fastener selection

Required thread length

$L_g \geq t_f + t_{\text{washer}} + t_{\text{nut}}$ [mm]

Fastener program

Fasteners					Tool
Group ¹⁾	Designation	Item no.	Standard threading ²⁾ L _g [mm]	Standard shank lengths ²⁾ L _s [mm]	Designation
M6	X-M6-20-27FP8	306079	20	27	DX 460, DX 351, DX 36, DX E72
W6	X-W6-20-22FP8	306073	20	22	DX 460, DX 351, DX 36, DX E72
	X-W6-20-27FP8	306074	20	27	DX 460, DX 351, DX 36, DX E72
	X-W6-38-27FP8	306075	38	27	DX 460, DX 36, DX E72
M8	X-M8-15-27P8	306092	15	27	DX 460, DX 36, DX E72
	X-M8-15-42P8	306094	15	42	DX 460, DX 36, DX E72
	X-M8-20-32P8	306096	20	32	DX 460, DX 36, DX E72
M10	M10-24-32P10	26413	24	32	DX 76, DX 76 PTR
W10	W10-30-27P10	26472	30	27	DX 600 N
	W10-30-32P10	26473	30	32	DX 600 N
	W10-30-42P10	26476	30	42	DX 600 N

¹⁾ Type threading: M = metric; W6, W10 = Whitworth 1/4"; 3/8"

²⁾ Standard threading and shank lengths. Other lengths and combinations available on special order.

Cartridge selection

Cartridge recommendation:

M6, W6, M8: **6.8/11M yellow or red cartridge**

M10: **6.8/18M blue or red**

W10: **6.8/18 yellow, red or black**


Tool energy adjustment by setting tests on site.

Fastening quality assurance

Fastening inspection


X-M6 / W6

Penetration depth



$$h_{ET} = L_s \pm 2$$


Tightening torque



$$T_{rec} \leq 4 \text{ Nm}$$


X-M8, M10, W10

Penetration depth



$$h_{ET} = L_s \pm 2$$

Tightening torque



$$T_{rec} \leq 6 \text{ Nm}$$